

ZHUNYI PRODUCT LIST --20240926

No.	Display Size (inch)	Display Resolution	View Direction	Active Area (mm)	LCM Outline Dimension (mm)	Thickness (mm)	Interface	Operating Temperature	Storage Temperature	Shape	Remarks	Remarks	Shared Product
1	1.3"	240*240	IPS	23.40*23.40	26.17*29.22	1.50	SPI	-20°C ~ 70°C	-30°C ~ 80°C	square	-		Z13001
2	1.3"	240*240	IPS	23.40*23.40	35.60*38.10	1.50	SPI	-20°C ~ 70°C	-30°C ~ 80°C	round	-	highly recommended	Z13008/Z13011
3	1.38"	240*240	IPS	35.14*35.14	35.14*35.14	1.60	SPI	-20°C ~ 70°C	-30°C ~ 80°C	round	-		
4	1.46"	360*360	IPS	36.94*36.94	39.30*40.96	1.60	SPI	-20°C ~ 70°C	-30°C ~ 80°C	round	-		Z14601
5	1.47"	172*320	IPS	17.65*32.83	19.65*36.76	1.60	MCU/RGB/SPI	-20°C ~ 70°C	-30°C ~ 80°C	rectangle	Round chamfer		Z15007
6	1.54"	240*240	IPS	27.72*27.72	31.50*35.00	1.90	MCU/SPI/MIPI	-20°C ~ 70°C	-30°C ~ 80°C	square	-		Z15002
7	1.6"	400*400	IPS	39.84*39.84	42.14*44.34	1.94	QSPI	-20°C ~ 70°C	-30°C ~ 80°C	round	-	highly recommended	Z16004
8	1.69"	240*280	IPS	27.97*32.63	30.07*37.43	1.90	MCU/RGB/SPI	-20°C ~ 70°C	-30°C ~ 80°C	rectangle	Round chamfer		Z17002
9	1.99"	170*320	IPS	22.7*42.72	25.1*49.47	1.50	MCU/RGB/SPI	-30°C ~ 85°C	-30°C ~ 85°C	rectangle			Z20005
10	2.0"	240*320	IPS	30.60*40.80	37.68*51.32	2.30	MCU/SPI/MIPI	-20°C ~ 70°C	-30°C ~ 80°C	4:3	-		Z20001
11	2.0"	480*360	IPS	40.82*30.62	46.10*40.96	2.53	MCU/RGB/MIPI	-20°C ~ 80°C	-30°C ~ 80°C	4:3	-		Z20004/Z20009
12	2.0"	320*240	IPS	40.8*30.6	46.10*40.96	2.53	MCU/RGB/SPI	-20°C ~ 70°C	-30°C ~ 80°C	4:3	-		Z20007
13	2.1"	480*480	IPS	53.28*53.28	56.18*59.71	2.30	RGB+SPI/MIPI	-20°C ~ 70°C	-30°C ~ 80°C	round	-		Z21009
14	2.4"	240*320	TN/IPS	36.72*48.76	40.52*57.00	2.40	MCU/SPI/RGB/MIPI	-20°C ~ 70°C	-30°C ~ 80°C	4:3	-	highly recommended	Z24009/Z24017/Z24023
15	2.5"	240*240	TN	45.07*45.07	50.58*56.18	2.40	MCU/SPI	-20°C ~ 70°C	-30°C ~ 80°C	square	-	highly recommended	Z25001
16	2.54"	160*144	IPS	48*43.2	54.56*53.56	2.30	MCU/RGB/SPI/MIPI	-20°C ~ 70°C	-30°C ~ 80°C	square	Not for sale		
17	2.73"	320*320	IPS	48.96*48.96	53.54*58.74	2.54	MCU/RGB/SPI/MIPI	-20°C ~ 70°C	-30°C ~ 80°C	square		highly recommended	Z27002
18	2.8"	240*320	IPS/TN	43.20*57.60	50.00*69.20	2.45	MCU/SPI+RGB/SPI	-20°C ~ 70°C	-30°C ~ 80°C	4:3	-		Z28017
19	2.8"	480*480	IPS	70.12*70.12	73.03*76.48	2.30	RGB+SPI/MIPI	-20°C ~ 70°C	-30°C ~ 80°C	round	-		Z28008
20	2.83"incell	400*800	IPS	32.10*64.20	34.40*69.35	2.10	QSPI/RGB/MIPI	-20°C ~ 80°C	-30°C ~ 80°C	2:1	Round chamfer	highly recommended	
21	3.0"	480*854	IPS	37.44*66.61	42.70*74.70	2.45	RGB+SPI/MIPI	-20°C ~ 70°C	-30°C ~ 80°C	16:9	-	highly recommended	Z30010/Z30032
22	3.4"	480*480	IPS	60.48*60.48	65.72*69.64	2.45	RGB+SPI/MIPI	-20°C ~ 70°C	-30°C ~ 80°C	square	-	highly recommended	Z34011/Z34012
23	3.4"	800*800	IPS	87.60*87.60	94.90*96.95	2.30	MIPI	-20°C ~ 70°C	-30°C ~ 80°C	round	-		Z34009
24	3.4"incell	540*960	IPS	42.00*74.72	44.30*79.87	2.10	QSPI/RGB/MIPI	-20°C ~ 80°C	-30°C ~ 80°C	16:9	Round chamfer	highly recommended	
25	3.36*3.5"	240*320	IPS	51.27*68.36	54.50*83.00	2.19	MCU/RGB/SPI	-20°C ~ 70°C	-30°C ~ 80°C	rectangle	-		Z35022
26	3.5"	320*240	IPS	70.08*52.56	76.78*63.74	3.20	RGB	-30°C ~ 85°C	-30°C ~ 85°C	4:3	-		Z35008
27	3.5"	320*480	IPS/TN	48.96*73.44	53.76*82.39	2.25	MCU/RGB+SPI/MIPI	-20°C ~ 70°C	-30°C ~ 80°C	3:2	-		Z35023
28	3.7"	240*960	IPS	22.86*91.44	25.30*98.89	1.61	MCU/RGB/MIPI	-20°C ~ 70°C	-30°C ~ 80°C	rectangle	-		Z37002
29	3.92"	320*320	IPS	71.14*69.82	74.86*76.73	2.17	MCU/RGB/SPI/MIPI	-20°C ~ 70°C	-30°C ~ 80°C	square	-		Z39001
30	3.95"	480*480	IPS	68.00*68.00	74.828*78.978	2.15	RGB+SPI/MIPI	-20°C ~ 70°C	-30°C ~ 80°C	square	-		Z40059/Z40069
31	3.95"	720*720	IPS	71.93*71.93	74.83*78.98	2.15	MIPI	-20°C ~ 70°C	-30°C ~ 80°C	square	-		Z40066/Z40065
32	3.97"incell	480*800	IPS	51.84*86.40	57.14*96.85	2.15	RGB+SPI/MIPI	-20°C ~ 70°C	-30°C ~ 80°C	4:3	-		Z40032
33	3.98"	320*480	IPS	55.68*83.52	60.88*94.57	2.30	MCU/RGB/MIPI	-20°C ~ 70°C	-30°C ~ 80°C	rectangle	-		Z40063/Z40064
34	4.0"	720*720	IPS	101.52*101.52	105.6*109.87	2.22	MIPI	-20°C ~ 70°C	-30°C ~ 80°C	round	-		Z40054

ZHUNYI PRODUCT LIST --20240926

No.	Display Size (inch)	Display Resolution	View Direction	Active Area (mm)	LCM Outline Dimension (mm)	Thickness (mm)	Interface	Operating Temperature	Storage Temperature	Shape	Remarks	Remarks	Shared Product
35	4.0"incell	480*1080	IPS	42.00*94.50	44.10*99.45	2.06	MIPI	-20°C ~ 80°C	-30°C ~ 80°C	rectangle	Round chamfer	highly recommended	Z40067
36	4.3"	480*272	IPS	95.04*53.86	105.46*67.16	2.75	RGB	-30°C ~ 70°C	-30°C ~ 80°C	9:16	-		Z43016/Z43014
37	4.3"	480*800	IPS	56.16*93.60	60.46*103.65	1.85	RGB+SPI/MIPI	-20°C ~ 70°C	-30°C ~ 80°C	4:3	-		Z43029
38	4.3"	800*480	IPS	95.04*53.86	105.4*67.1	3.00	RGB/LVDS	-20°C ~ 70°C	-30°C ~ 80°C	Landscape	-		Z43081
39	4.6"	320*960	IPS	36.708*110.304	41.568*118.8	2.50	MCU/RGB/MIPI	-30°C ~ 85°C	-30°C ~ 85°C	Bar	-		Z46009
40	5.0"	800*480	IPS	108.00*64.80	120.70*75.80	3.00	RGB	-20°C ~ 70°C	-30°C ~ 80°C	Landscape	-		Z49445
41	5.0"	480*854	IPS	61.33*109.65	66.40*120.05	2.25	RGB+SPI/MIPI	-20°C ~ 70°C	-30°C ~ 80°C	16:9	-		CD050396/Z49399
42	5.0"incell	720*1280	IPS	62.10*110.40	64.40*115.45	2.10	MIPI	-20°C ~ 80°C	-30°C ~ 80°C	16:9		highly recommended	Z49433
43	5.0"	1080*1080	IPS	127.00*127.00	136.53*132.10	2.00	MIPI	-20°C ~ 70°C	-30°C ~ 80°C	round	-		
44	5.0"	600*600	IPS	89.28*89.28	95.08*99.5	2.70	MIPI	-20°C ~ 70°C	-30°C ~ 80°C	square	-		Z50075
45	5.5"	720*1280	IPS	68.04*120.96	71.00*130.20	1.65	MIPI	-20°C ~ 70°C	-30°C ~ 80°C	16:9	-	highly recommended	Z55290
46	5.7"	640*480	IPS	115.20*86.40	127.00*98.43	5.60	LVDS/RGB/MIPI	-30°C ~ 80°C	-30°C ~ 80°C	3:2	-		Z57013
47	6.0"	720*1480	IPS	66.74*137.19	70.80*145.50	2.25	MIPI	-20°C ~ 70°C	-30°C ~ 80°C	18:9	-	highly recommended	Z60040
48	6.75"/6.86"	480*1280	IPS	60.19*160.51	65.78*171.75	2.60	MIPI	-20°C ~ 70°C	-30°C ~ 80°C	Bar	-		Z686007
49	6.75"/6.9"	720*1440	IPS	78.02*156.04	81.71*163.34	2.35	MIPI	-20°C ~ 70°C	-30°C ~ 80°C	18:9	-	highly recommended	Z69007
50	6.9"	280*1424	IPS	33.6*170.88	38.2*181.47	3.45	MIPI	-20°C ~ 70°C	-30°C ~ 80°C	Bar	-		Z69005
51	6.95"incell	600*1024	IPS	89.28*152.37	95.00*163.20	2.55	MIPI	-10°C ~ 50°C	-20°C ~ 60°C	16:9	-	highly recommended	CD0695025/Z70027
52	7.0"	800*480	IPS/TN	154.21*85.92	165.00*100.00	5.70	RGB	-20°C ~ 70°C	-30°C ~ 80°C	Landscape	-		
53	7.0"	1024*600	IPS/TN	154.21*85.92	163.70*96.90	2.55	LVDS/RGB/MIPI	-20°C ~ 70°C	-30°C ~ 80°C	Landscape	-		Z70078/Z70069/Z70017
54	7.84	400*1280	IPS	190.08*59.40	205.76*67.76	4.54	MIPI	-20°C ~ 70°C	-30°C ~ 80°C	Bar	-		Z784001
55	8.0"incell	800*1280	IPS	107.64*172.22	114.66*184.16	2.65	MIPI	-20°C ~ 70°C	-30°C ~ 80°C	16:9	-	highly recommended	Z80008/Z80022
56	8.0"	1200*1920	IPS	107.64*172.22	114.66*184.16	2.65	MIPI	-20°C ~ 60°C	-30°C ~ 70°C	rectangle	-		Z80035
57	8.9"/9.0"	800*1280	IPS	119.28*190.85	125.48*202.90	2.60	MIPI	-20°C ~ 70°C	-30°C ~ 80°C	16:9	-	highly recommended	Z90010/Z90017
58	10.1"	1024*600	IPS	222.72*125.28	235.1*143.2	4.30	LVDS	-20°C ~ 70°C	-30°C ~ 80°C	Landscape	-		Z101051
59	10.1"incell	800*1280	IPS	135.36*216.58	143.00*228.50	2.60	MIPI	-10°C ~ 60°C	-20°C ~ 70°C	16:9	-		Z101029
60	10.1"	1280*800	IPS	216.96*135.60	224.02*147.76	2.60	LVDS	-20°C ~ 70°C	-30°C ~ 80°C	9:16	-	highly recommended	Z101035
61	10.1"incell	1200*1920	IPS	135.36*216.58	143.06*228.56	2.60	MIPI	-10°C ~ 60°C	-20°C ~ 70°C	16:9	-		Z101039
62	10.1"	1920*1200	IPS	218.61*135.50	224.02*147.76	2.60	LVDS	-20°C ~ 70°C	-30°C ~ 80°C	9:16	-		Z101046
63	10.25"incell	1920*720/720*1920	IPS	243.65*91.37	265.2*109.8	6.50	LVDS双8	-20°C ~ 70°C	-30°C ~ 80°C	Landscape	-	highly recommended	Z102502/Z102503
64	10.36"incell	1200*2000	IPS	135.36*225.60	140.36*234.63	2.10	MIPI	-20°C ~ 70°C	-30°C ~ 80°C	16:9	-		Z101028
65	12.1"	1280*800	IPS	261.12*163.2	275.85*179.15	5.60	LVDS	-20°C ~ 70°C	-30°C ~ 80°C	Landscape	-		Z121002
66	15.6"	1920*1080	IPS	344.16*193.59	350.66*214.79	2.80	EDP	0°C ~ 50°C	-20°C ~ 60°C	Landscape	-	highly recommended	Z156004
67	15.6"	1920*1080	IPS	344.16*193.59	351*86*206.33	3.20	LVDS	0°C ~ 50°C	-20°C ~ 60°C	Landscape	-		Z156006